



TECHNICAL SPECIFICATION

Khorasan Electric Ind. Co.



Power Cable 2 x 1.5 (N)YMHY					
P.V.C - insulated & Sheathed, Multi-Core Cable with Flexible Conductor Type NYMHY, 300/500 V ACC(ISIRI 607-5) H05VV-F					
Cable Layer Construction	CU , PVC , PVC		LV		
Applicable Standard(s)	IEC 60227 & ISIRI 607-5 & IEC 60228				
Description		Unit	Specification		
CONDUCTOR	CU	Material	****	Plain Annealed Copper	
		TYPE	****	Flexible (Class 5) RF	
		No.of core & Conductor Area	L	no (mm ²)	1 x 1.5
			N		1 x 1.5
			PE		0
		No & Dia of Wire	L	no (mm)	30 x 0.24
			N		30 x 0.24
PE	0				
Shape	****	ROUND			
INSULATION	PVC	Material	****	Extruded PVC	
		Thickness	L	0.7	
			N	0.7	
			PE	0.0	
Colour	****	L:Black , N:Blue			
Outer Sheath	PVC	Material	****	Extruded PVC	
		Thickness	mm	0.8	
		Colour	****	Black	
Overall diameter (Approx.)		mm	7.44		
Cable Weight (Approx.)		Kg / km	84.76		
Packing		****	Drum		
Rated Voltage U ₀ /U (Um)		V	300 / 500		
System Frequency		Hz	50		
DC conductor resistant At 20 °C		Ω/ Km	13.3		
Conductor Short Circuit Current (1 Sec)		KA	0.167		
Test voltage		KV	2		
Max.Short circuit withstand current temperature		°C	+ 160		
Operation temperature		°C	- 30 to +70		
Special Proerties		Flame Retardant	IEC 60332-1-2		

(افشار مشهد) KHORASAN ELECTRIC IND.CO ISIRI(607)53 6950387946 H05VV-F 300/500 V NYMHY 2x1.5 mm2 MADE IN IRAN CE