



TECHNICAL SPECIFICATION

Khorasan Electric Ind. Co.



Power Cable 4 x 0.75 (N)YMHY

P.V.C - insulated & Sheathed, Multi-Core Cable with Flexible Conductor Type NYMHY, 300/500 V ACC(ISIRI 607-5) H05VV-F

Cable Layer Construction	CU , PVC , PVC	LV
Applicable Standard(s)	IEC 60227 & ISIRI 607-5 & IEC 60228	

Description		Unit	Specification	
CONDUCTOR	Material	****	Plain Annealed Copper	
	TYPE	****	Flexible (Class 5) RF	
	No.of core & Conductor Area	L	no (mm ²)	3 x 0.75
		N		1 x 0.75
		PE		0
	No & Dia of Wire	L	no (mm)	24 x 0.2
		N		24 x 0.2
PE		0		
Shape	****	ROUND		
INSULATION	Material	****	Extruded PVC	
	Thickness	L	0.6	
		N	0.6	
		PE	0.0	
Colour	L:Black, Yellow, Red, N:Blue			
Outer Sheath	Material	****	Extruded PVC	
	Thickness	mm	0.8	
	Colour	****	Black	
Overall diameter (Approx.)		mm	7.24	
Cable Weight (Approx.)		Kg / km	79.85	
Packing		****	Drum	
Rated Voltage U ₀ /U (Um)		V	300 / 500	
System Frequency		Hz	50	
DC conductor resistant At 20 °C		Ω/ Km	26	
Test voltage		KV	2	
Max.Short circuit withstand current temperature		°C	+ 160	
Operation temperature		°C	- 30 to +70	
Special Proerties		Flame Retardant	IEC 60332-1-2	

(افشار مشهد) KHORASAN ELECTRIC IND.CO ISIRI(607)53 6950387946 H05VV-F 300/500 V NYMHY 4x0.75 mm2 MADE IN IRAN CE