



TECHNICAL SPECIFICATION

Khorasan Electric Ind. Co



Cable 4 x 2.5 (N)YSLCY						
Cable Laye C onstruction		CU , PVC, Al-Pet , CWB , PVC			LV	
S tandard Matching		IEC 60227-7 , DIN VDE 0245				
R	D e s c r i p t i o n			U n i t	S p e c i f i c a t i o n	
1	Conductor	CU	Material	***	Annealed Copper	
			Conductor Type	***	Flexible (Class 5) RF	
			Nominal Cross Section	L	mm ²	3 x 2.5
				N	mm ²	1 x 2.5
				PE	mm ²	0
			Number & Diameter of wires	L	no * mm	50 x 0.24
				N	no * mm	50 x 0.24
PE	no * mm	0				
Shape	***	Round				
2	Insulation	PVC	Material	***	Extruded PVC	
			Thickness	L	mm	0.8
				N	mm	0.8
				PE	mm	0.0
Colour	PH: Black,Red,Yellow,N:Blue					
3	Wrapping	AL-Pet	Material	***	Polyester Tape	
			Thickness	mm	0.036	
			Material	***	Aluminum	
			Thickness	mm	0.036	
4	Shield	CWB	Material	***	Annealed Copper	
			Number & diameter of wires	mm	24 x 6 x 0.12	
5	Outer Sheath	PVC	Material	***	Extruded PVC	
			Thickness	mm	1.2	
			Colour	****	Gray	
6	Approx. overall diameter of cable			mm	11.44	
7	Approx. Weight of cable			K g /k m	198	
8	Packing			****	Drum	
9	Rated Voltage U0 / U(Um)			V	300 / 500	
10	System Frequency			H z	50	
11	Max conductor resistance At 20° C			Ω/ K m	7.98	
12	Short circuit withstand current / time5s			K A	0.2	
13	Cable Voltage test			K V	2	
14	Max.Short circuit withstand current temperature			°C	+ 160	
15	Operation temperature			°C	-30 to +70	

(افشارنژاد) KHORASAN ELECTRIC IND.CO 300 /500 (N)YSLCY 4x2.5 mm RF FLEXIBLE MADE IN IRAN CE