



TECHNICAL SPECIFICATION

Khorasan Electric Ind. Co.



Wire 1 x 35 (N)YAF

P.V.C - insulated ,non Sheathed,Single-Core Cable with Flexible Conductor For internal Wiring, 450/750 V ACC.ISIRI(607)02

Cable Layer Construction	CU , PVC		LV
Applicable Standard(s)	IEC 60227 & ISIRI 607 & IEC 60228 & DIN VDE 0295		
Description		Unit	Specification
CONDUCTOR	CU	Material	**** Plain Annealed Copper
		TYPE	**** Flexible (Class 5) RF
		No.of core & Conductor Area	no (mm ²) 1 x 35
		No & Dia of Wire	no (mm) 266 x 0.39
		Shape	**** ROUND
INSULATION	PVC	Material	**** Extruded PVC
		Thickness	mm 1.2
		Colour	**** Yellow : Green
Overall diameter (Approx.)		mm	10.4
Cable Weight (Approx.)		Kg / km	350
Packing		****	Drum & Reel
Rated Voltage Uo/U		V	450 / 750
System Frequency		Hz	50
DC conductor resistant At 20 °C		Ω/ Km	0.554
Test voltage		KV	2.5
Max.Short circuit withstand current temperature		°C	+ 160
Operation temperature		°C	- 30 to +70
Special Proerties		Flame Retardant	IEC 60332-1-2
(افشارراد) KHORASAN ELECTRIC IND.CO ISIRI(607)02 6950954946 H07V-K 450/750V 1x35 mm2 RF MADE IN IRAN CE			

Shafiei