

# XS<sup>3</sup> Circuit breaker 4500

Thermal magnetic circuit breakers B and C curve from 6 A to 63 A



4 032 04



4 032 17

Works in accordance with the following standards IEC 60898-1  
Breaking capacity:

4500 - IEC 60898-1 - 230/400 V~  
4.5 kA - IEC 60947-2 - 230/400 V~  
DX<sup>3</sup> Can be equipped with auxiliary contacts.

Single Pole 230/400 V~			3 Poles 400 V~			
Amb.	Ref.	Nominal values I <sub>n</sub> (A)	Number of modules	B curve	Nominal values I <sub>n</sub> (A)	Number of modules
10	4 032 02	6	1	3	4 032 15	3
10	4 032 03	10	1	3	4 032 16	3
10	4 032 04	16	1	3	4 032 17	3
10	4 032 05	20	1	3	4 032 18	3
10	4 032 06	25	1	3	4 032 19	3
10	4 032 07	32	1	3	4 032 20	3
10	4 032 08	40	1	3	4 032 21	3
10	4 032 09	50	1	3	4 032 22	3
10	4 032 10	63	1	3	4 032 23	3

  

Single Pole 230/400 V~			3 Poles 400 V~			
Amb.	Ref.	Nominal values I <sub>n</sub> (A)	Number of modules	C curve	Nominal values I <sub>n</sub> (A)	Number of modules
10	4 033 27	6	1	3	4 033 40	3
10	4 033 28	10	1	3	4 033 41	3
10	4 033 29	16	1	3	4 033 42	3
10	4 033 30	20	1	3	4 033 43	3
10	4 033 31	25	1	3	4 033 44	3
10	4 033 32	32	1	3	4 033 45	3
10	4 033 33	40	1	3	4 033 46	3
10	4 033 34	50	1	3	4 033 47	3
10	4 033 35	63	1	3	4 033 48	3